

Table of Contents

- 1. Stylesheets** 2
 - 1.1 Keep managed and author styles separate 2
 - 1.2 Load the cascade in order 2
 - 1.3 Put a change in the narrowest file 3
 - 1.4 Keep the managed stylesheets up to date 4
- Index** 6

1. Stylesheets

Stylesheets control the appearance of a document beyond the options exposed by Zensical and Prodockit. This is an advanced feature: use it when a configuration setting cannot make the required change.

1.1 Keep managed and author styles separate

The stylesheet ownership rules separate styles Prodockit maintains from styles that belong to the document author. Keep that separation when changing colours, spacing, fonts, or the PDF presentation:

[Table 33.1](#) assigns each stylesheet to either prodockit or the document author.

Table 1.1. Keep managed and author styles separate

File	Owner	Applies to
docs/stylesheets/pdk.css	Prodockit	Website and PDF component defaults
docs/stylesheets/extra.css	Document author	Website and PDF additions or overrides
docs/stylesheets/pdk-pdf.css	Prodockit	PDF-only presentation defaults
docs/stylesheets/print.css	Document author	PDF-only additions or overrides

The two `pdk` files are delivered with Prodockit and checked by [prodockit pins](#). Do not edit them: an update replaces them with the release's current defaults. Add your own rules to `extra.css` or `print.css` instead. Those two author-owned files are not shared, pinned, or replaced by `template-sync`.

1.2 Load the cascade in order

The website theme and PDF renderer provide the foundations for their respective outputs. Prodockit's managed styles and the author's styles then load in the order shown below. A rule in `extra.css` therefore changes both outputs, while a rule in `print.css` changes only the PDF and has the final say when selectors have equal specificity. A final internal guard protects only the page canvas and removes website navigation from the PDF; it does not set the document's colours, typography, tables, contents presentation, or component spacing.

[Table 33.2](#) shows the order in which the website and PDF stylesheets are loaded and which output uses each file.

Table 1.2. Load the cascade in order

Output	Styles loaded, from first to last
Website	Theme → <code>pdk.css</code> → <code>extra.css</code>
PDF	Renderer foundations → <code>pdk.css</code> → <code>extra.css</code> → <code>pdk-pdf.css</code> → <code>print.css</code>

The arrows show which later layer can override an earlier layer at equal CSS specificity. The website leaves the cascade after `extra.css` ; the PDF continues through its two PDF-only files:

Website stylesheet cascade

The website stops at the author override shown in [Figure 33.1](#).



Figure 1.1. Website stylesheet cascade

PDF stylesheet cascade

[Figure 33.2](#) continues the same cascade through the two print-only layers.



Figure 1.2. PDF stylesheet cascade

Implement the cascade by listing the files in this order in `zensical.toml` :

```

[project]
extra_css = [
  "stylesheets/pdk.css",
  "stylesheets/extra.css",
]

[project.extra]
pdf_extra_css = [
  "stylesheets/pdk-pdf.css",
  "stylesheets/print.css",
]
  
```

1.3 Put a change in the narrowest file

Choose the author-owned stylesheet whose scope matches the output being changed:

- Use `extra.css` when the website and PDF should look alike.
- Use `print.css` when the change applies only to paginated output.

- Propose a change to Prodockit when every project should receive it; do not make that change directly in either `pdk` file.

For example, this makes level-three entries in the PDF contents page more widely spaced without changing the website:

```
/* docs/stylesheets/print.css */
#TOC > ul > li > ul > li > ul > li {
  line-height: 1.15 !important;
}
```

1.4 Keep the managed stylesheets up to date

Follow [Staying in step with the template](#) to receive new versions of `pdk.css` and `pdk-pdf.css` alongside the template's other maintained files. `prodockit template-sync` previews the changes before they are applied.

Run `prodockit pins --check` to compare the two managed stylesheets with the installed release. If `template-sync` finds local edits in either one, it prints a managed-stylesheet warning and keeps the local file. Move intentional rules into `extra.css` or `print.css`, then restore the managed file using the exact `--force FILE-PATH` command shown by the report.

Index

S

stylesheets

 stylesheet ownership, 2